

Compact, agile and high-performing

The Kränzle Ventos wet and dry vacuum cleaners

- Folding ergonomically shaped carrying handle
- Large wheels with rigid steel axle
- Power tool electrical socket with switch-on and cut-out delay
- Electronic suction power control
- 7.5 m rubber-coated power lead with cable reel
- Exhaust air ventilation connection
- Cut-out electrodes
- Useful storage board for standard accessories





Technical specifications

	Ventos 20 E/L	Ventos 30 E/L
Ord. no.	58,391 0	58,393 0
Connected load	230 V, 50/60 Hz	230 V, 50/60 Hz
Power intake / Appliance socket	400 - 1200 W / 2400 W	400 - 1200 W / 2400 W
Fuse	16 A	16 A
Volume flow max. (turbine)	3,700 l/min	3,700 l/min
Vacuum max. (turbine)	24,000 Pa, 240 mbar	24,000 Pa, 240 mbar
Sound pressure level	72 dB (A)	72 dB (A)
Container volume	17 l	32 l
Max. filling volume when vacuuming water	ca. 6 l	ca. 17 l
Protection type	IP x 4	IP x 4
Dust classification	L	L
Weight without accessories	9.4 kg	9.9 kg
Dimensions (L x W x H) in mm	485 x 380 x 445	485 x 380 x 550

Features & Equipment

	Ord. no.	Ord. no.
Suction hose Ø 36 mm x 3,5 m	(45,281 9)	(45,281 9)
Floor nozzle, with separate rubber lips for wet vacuum cleaning	(58,402 1)	(58,402 1)
2 extensions 500 mm each, stainless steel	(58,403 0)	(58,403 0)
Main filter cartridge made of PES fibrous web	(45,440 3)	(45,440 3)
1 dust bag	(45,440 0) 5 pcs.	(45,440 1) 5 pcs.
Hand pipe, angled	(58,402 9)	(58,402 9)
Flat nozzle 300 mm	(58,402 3)	(58,402 3)
Upholstery nozzle	(58,400 9)	(58,400 9)
Suction brush	(58,400 8)	(58,400 8)